Improving client systems security with Qubes OS

Marek Marczykowski-Górecki, Invisible Things Lab

4 Jul 2016

We need secure client systems

æ

★ 문 ► ★ 문 ►

< A >

We need secure client systems

Otherwise no security really works:

∃ ► < ∃ ►</p>

We need secure client systems

Otherwise no security really works:

- Encryption
- 2-factor authentication
- "Secure cloud"

All the above can be manipulated by compromised client system.

Current, monolithic systems

• All the drivers, services part of TCB

э

- All the drivers, services part of TCB
 - Networking DHCP client, Wifi

- All the drivers, services part of TCB
 - Networking DHCP client, Wifi
- Every application have access to all the user data

- All the drivers, services part of TCB
 - Networking DHCP client, Wifi
- Every application have access to all the user data
 - PDF viewer

- All the drivers, services part of TCB
 - Networking DHCP client, Wifi
- Every application have access to all the user data
 - PDF viewer
 - Web browser

- All the drivers, services part of TCB
 - Networking DHCP client, Wifi
- Every application have access to all the user data
 - PDF viewer
 - Web browser
 - Mail client

- All the drivers, services part of TCB
 - Networking DHCP client, Wifi
- Every application have access to all the user data
 - PDF viewer
 - Web browser
 - Mail client
- Lack of GUI separation

- All the drivers, services part of TCB
 - Networking DHCP client, Wifi
- Every application have access to all the user data
 - PDF viewer
 - Web browser
 - Mail client
- Lack of GUI separation
- One bug to rule them all



Compartmentalization

• Separate each component from each other

∃ ► < ∃ ►</p>



Compartmentalization

- Separate each component from each other
- Divide the whole system into security domains

- ∢ ⊒ →



Compartmentalization

- Separate each component from each other
- Divide the whole system into security domains
- Use virtualisation, have minimal, simple interfaces

글 > - < 글 >





・ロン ・部 と ・ ヨ と ・ ヨ と …

Isolated devices

• Net VM

<ロ> <同> <同> < 同> < 同>



Isolated devices

- Net VM
- USB VM

(日) (四) (日) (日)



Isolated devices

- Net VM
- USB VM
- GUI VM (planned)

・ロン ・部 と ・ ヨ と ・ ヨ と …



Isolated data

- Different areas of digital life
- Different levels of trust

Not only about separating applications!

글 🖌 🖌 글 🕨

э



Isolated workflows

- Proxy VM (VPN, Tor, Whonix)
- Data converters (PDF, images)
- Data storage (offline vaults, gpg)
- Disposable VM

글 > - < 글 >

э



Framework for building secure workflows

- Socket-like inter-VM communication (qrexec)
- Each operation requires policy approval (not necessary user approval)
- VMs building blocks

글 > - < 글 >



Dedicated USB VM

æ

A 10



- Dedicated USB VM
- Untrusted, no user data

э

() <) <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <)
() <



- Dedicated USB VM
- Untrusted, no user data
- Services for specific applications



- Dedicated USB VM
- Untrusted, no user data
- Services for specific applications



- Dedicated USB VM
- Untrusted, no user data
- Services for specific applications

Supported devices

• Block devices - can be attached to any VM



- Dedicated USB VM
- Untrusted, no user data
- Services for specific applications

Supported devices

- Block devices can be attached to any VM
- Input devices strictly filtered (mouse only/mouse+keyboard)



- Dedicated USB VM
- Untrusted, no user data
- Services for specific applications

Supported devices

- Block devices can be attached to any VM
- Input devices strictly filtered (mouse only/mouse+keyboard)
- Generic USB passthrough



• Like software-based smartcard

æ

▲圖 ▶ ▲ 臣 ▶ ▲ 臣 ▶



- Like software-based smartcard
- Better control

3



- Like software-based smartcard
- Better control
- Audit trail

▲御▶ ▲理▶ ▲理≯



- Like software-based smartcard
- Better control
- Audit trail
- /bin/gpg drop-in replacement

伺 ト イヨト イヨト



<ロ> (四) (四) (三) (三) (三) (三)





э



• Network devices in separate VMs

э

∃ ► < ∃ ►</p>



- Network devices in separate VMs
- Dom0 has no network at all!

< E

э



- Network devices in separate VMs
- Dom0 has no network at all!
- VMs can be chained (proxy)

э

э



- Network devices in separate VMs
- Dom0 has no network at all!
- VMs can be chained (proxy)
- VPN, Tor, IDS, and many more



(日)

Qubes 3.x

- Qubes 3.1 released in March 2016
- Qubes 3.2-rc1 released last month

Supports everything mentioned here.

- ∢ ≣ ▶

Qubes 3.x

- Qubes 3.1 released in March 2016
- Qubes 3.2-rc1 released last month

Supports everything mentioned here.

Management stack

- Powerful framework for building secure client system.
- Sample recipes provided
- We need more!

∃ ► < ∃ ►</p>

Qubes Master Signing Key

427F 11FD 0FAA 4B08 0123 F01C DDFA 1A3E 3687 9494

Questions?

Marek Marczykowski-Górecki, Invisible Things Lab Improving client systems security with Qubes OS

< □ > < 同 >

æ

★ 문 ► ★ 문 ►

Thanks!

▲□▶ ▲□▶ ▲ □▶

æ

_ र ≣ ≯